



UV PRINT SUPER JEWEL CASE



PRINT REQUIREMENTS


-  Print file in PDF.
-  Use CMYK colour mode.
-  **DPI** Resolution: 300 dpi, scale 1:1.
-  Delete all template lines from the print file; leave crop marks only.
-  **3MM** Ensure that 3mm bleeds are added around the artwork.
-  **320%** Maximum ink levels: 320%.



TIPS FROM OUR PRINTHOUSE

-  **UV print uses CMYK paints, that are transparent. If you want to have non transparent print on transparent surface, there has to be a white base below the artwork.**
-  Gray separations: If you want black and white artwork, create grayscale using only the black channel (K).
-  Letters should be larger than 6p; below that size, we can't guarantee sharp printed letters, especially for thin or light fonts.
-  Letters look better in vector format rather than bitmap.
-  Black letters will be sharper when made solely of 100%K and set to overprint.

It is a digital printing technique similar to ink printing with the difference that the prints are fixed with UV light. The print is hardened, leaving a thin layer of colored and durable plastic on the surface of the material. As a result the print may have a delicate rough structure – where there is more paint or there is a dark color, the print may be more convex.
-  Due to the necessity to print in special forms, shifts in printing are possible and the paint may spread unevenly – one print may be slightly different from the other. If the cassettes are fully printed, ink traces may also appear on the edges and even on the tape.
-  If you do not like this character, think about tampography (for example, sharp contours are better for tampography).
-  In UV printing it is not possible to use colors from the pantone palette. We print using 4 colors (CMYK) with white undercoat or only white undercoat.



142 mm

123 mm

BACK